

NP1



**PAG AR124NPD
Model 9793**

4 x NP1 pockets
4 x PP90 sockets
Ni-Cd, Ni-MH & Li-Ion
4.8 to 14.8V, 1 to 10Ah
Discharger

Snap-on



**PAG PULSAR
Model 9795**

4 x Snap-on compatible
4 x PP90 sockets
Ni-Cd, Ni-MH & Li-Ion
4.8 to 14.8V, 1 to 10Ah
Discharger & Talk-Circuits

Snap-on



**PAG QUASAR
Model 9753**

2 x Snap-on compatible
2 x PP90 sockets
Ni-Cd, Ni-MH & Li-Ion
4.8 to 14.8V, 1 to 10Ah
Camera Power Supply

Snap-on



**PAG QUASAR
Model 9727**

2 x Snap-on compatible
2 x PP90 sockets
Ni-Cd, Ni-MH & Li-Ion
4.8 to 14.8V, 1 to 10Ah

V-Mount



**PAG V4-CPA
Model 9701V**

Camera Power Adaptor
For use with PAG Cube and V4-iPC chargers
Outputs 16.8V at 5.5A
Requires Model 9450 XLR-4 male to female connector.

Chip-Upgrades

PAG chargers are forward compatible. Older models can be upgraded to charge new batteries by purchasing a chip upgrade kit.

PAG AR Series 2 Chip-Upgrade for 9792, 9793, 9794 and 9795 (green or yellow labels) for charging all PAG Li-Ion batteries, including L95e.
Model 9670E

Quasar Chip-Upgrade for charging PAG L95e batteries.
Model 9670QE

PAG Chargers at a Glance.

No:	Name:	Connectors:	Connectors:	Size:	Weight:	Special Features:
9792	PAG AR124PLD	4 x PAGlok connectors	4 x PP90	82 x 168 x 240mm	1.23kg	Discharge Program
9752	PAG QUASAR	2 x PAGlok connectors	2 x PP90	72 x 135 x 185mm	0.88kg	Power Supply
9726	PAG QUASAR	2 x PAGlok connectors	2 x PP90	72 x 135 x 185mm	0.88kg	
9613	PAG Freelancer	2 x PAGlok connectors	-	55 x 115 x 135mm	0.41kg	
9702V	PAG Cube	4 x V-Mount Connectors	-	157 x 157 x 157mm	1.19kg	Intelligent Parallel Charging
9613V	PAG V2	2 x V-Mount Connectors	-	72 x 112 x 133mm	0.43kg	
9793	PAG AR124NPD	4 x NP1 pockets	4 x PP90	78 x 142 x 240mm	1.07kg	Discharge Program
9795	PAG PULSAR	4 x Snap-on compatible	4 x PP90	82 x 168 x 240mm	1.23kg	Discharge Program & Talk Circuits
9753	PAG QUASAR	2 x Snap-on compatible	2 x PP90	80 x 135 x 185mm	0.84kg	Power Supply
9727	PAG QUASAR	2 x Snap-on compatible	2 x PP90	80 x 135 x 185mm	0.84kg	

PAG 24V to 30V Ni-Cd Chargers.

PAG continues to manufacture 30V AR Series chargers optimised for charging 24V to 30V Ni-Cd batteries. They are available in single or four-channel models and incorporate XLR-4 (M) connectors.

Contact the PAG Sales Department for information about PAG 30V AR Series Chargers.

