

Paglight Kits incorporating Pagbelt NMH.

Paglight Kits are designed to provide everything required for a lighting source that can be used either on or off camera.

The Paglight incorporates a standard halogen lamp holder and a choice of 2 bi-pin halogen lamps (20W, 35W, 50W, 75W or 100W). The light is fitted with a professional accessory holder that includes a daylight filter, a diffuser and two parallel barn doors. A handle is included for off-camera use. A stud adaptor and a camera shoe plate are included for mounting the light to the camera. The XLR-4 Power Base enables the Paglight to be powered from the battery belt supplied.

The **Pagbelt NMH** battery belt is a 10Ah power source, available in 12V or 13.2V formats, ideal for powering lights of up to 100W. It incorporates an integral overnight charger.

Paglight Kits are supplied in a fitted flight case and comprise:

- > Paglight (12V).
- > XLR-4 Power Base (length 1.5m).
- > Standard Lamp Holder.
- > A choice of 2 lamps (20W, 35W, 50W, 75W or 100W).
- > Rotatable Accessory Kit comprising: 1 accessory ring, 1 pair of parallel barn doors, 1 dichroic filter and 1 diffuser.
- > Pagbelt NMH with integral overnight charger and a power lead suitable for country of use.
- > Handle.
- > Camera shoe plate 1/4" Whit.
- > Stud adaptor 1/4" Whit.

Paglight/Pagbelt NMH Kits

Model 9875N	12V 10Ah
Model 9878N	13.2V 10Ah



Paglight LED & PowerArc Field Kits.

There are two **Paglight Field Kits** one that incorporates the PAG PowerArc HMI unit and one that incorporates the PAG LED Dimmer Unit. Each includes two standard halogen units, enabling you to take full advantage of the unique plug-in lamp holder system that makes Paglight the industry's most versatile camera light. Converting the Paglight from halogen to Arc or LED takes a matter of seconds.

The kit is tailored to your requirements with a choice of Power Base, suitable for the light output on most cameras (PP90, D-Tap or XLR-4), and a choice of two halogen lamps (20W, 35W, 50W, 75W or 100W).

The light is fitted with a rotatable accessory holder that includes a daylight filter, a diffuser and two parallel barn doors. A dichroic filter that converts the light output to match halogen is included for use with the PowerArc and the LED unit.

A stud adaptor and a camera shoe plate are included for mounting the light to the camera. A Camera Clamp is included for mounting the Paglight to a camera handle, or off-camera. A handle is included for handheld use.

The components are housed in a strong, lightweight and compact fitted flight case.

The Paglight PowerArc and LED Field Kits comprise:

- A** Paglight 12V.
- B** Choice of Power Base (PP90, D-Tap or XLR-4).
- C** Standard Lamp Holder (with choice of lamp 20W, 35W, 50W, 75W or 100W).
- D** Standard Lamp Holder and protector (with choice of lamp).
- E** PowerArc Unit (with arc lamp or LED Dimmer Unit and lamp protector).
- F** Rotatable Accessory Kit comprising: accessory holder, 1 pair of parallel barndoors, 1 dichroic filter and 1 diffuser.
- G** Tapered Barndoors.
- H** PowerArc or LED Conversion Filter.
- I** Handle 1/4" Whit. bush / stud.
- J** Camera Clamp 1/4" Whit. bush.
- K** Camera Shoe Plate 1/4" Whit.
- L** Stud Adaptor 1/4" Whit.
- M** Fitted Flight Case.
- N** Storage space for additional components.

Paglight LED Field Kit

Model	Size	Weight
9825L	468 x 386 x 109mm	3kg

Paglight PowerArc Field Kit

Model	Size	Weight
9825	468 x 386 x 109mm	3kg

