

## NEW PRODUCT DATA SHEET

# PAGlink Micro Charger AC/DC

ULTRA-COMPACT V-MOUNT TRAVEL CHARGER



## DESCRIPTION

The PAGlink Micro Charger is ideal when you want to travel light and charge PAGlink V-Mount batteries. This ultra-compact, inexpensive charger is small enough to fit in any camera bag. It accepts 5-20V DC input, and can be powered from a variety of sources, making it the ideal travel charger.

The Micro Charger will charge PAGlink V-Mount batteries of any rated capacity, and from any state of charge, individually or linked. It can also be used for charging non-linking V-Mount Li-Ion batteries manufactured by PAG and Sony.

PAGlink is the first camera battery system that allows batteries to be linked for charging. At the end of a shoot, simply link your batteries and connect them to the charger. The next day, they will be fully charged and ready to go, without intervention.

If you need power in a hurry, one fully discharged 96Wh battery will be 80% charged in approximately 3 hours. Two fully-discharged 96Wh PAGlink batteries will be fully-charged in approximately 8 hours.

The charge status of each battery is shown on its individual display. The most-discharged batteries are given priority until all the batteries are in a similar state of charge; they are then fully-charged simultaneously. The charger features LED indication of charging, charge completion, an absent battery and a faulty battery.

The Micro Charger can be powered using the Power Supply Unit included, which accepts 100-240V AC input, converted to



CHARGER

AC POWER SUPPLY UNIT



USB POWER CABLE

IN-CAR POWER CABLE

low-voltage DC. A power plug of your choice is included which is interchangeable with other options that enable direct connection to worldwide AC outlets.

The charger can also be powered from a 12V vehicle battery, via the dashboard lighter socket, or a USB charger (2A) using the DC power cables included.

## SPECIFICATION

### PAGlink Micro Charger Model 9713V

#### Suitable Batteries:

*Individual or linked charging, from any state of charge:*  
PAGlink V-Mount Batteries Models 9303, 9304, 9308 & 9309.

#### *Individual charging only:*

PAG V-Mount Batteries Models 9307V, 9310V and 9305V.  
Sony V-Mount Li-Ion Batteries.

#### PAGlink Charging:

The Micro Charger is designed for charging simultaneously up to 4 linked PAGlink batteries, of any rated capacity, from any state of charge.

#### Recovery Charge:

Automatically recovers a Li-Ion battery after shut down.

**Input:** DC 5V to 20V (2A). Connector: 2.1mm DC (PP90).  
Power Supply Unit: AC 100-240V ~ autoselected. Frequency 50-60 Hz. Maximum power consumption 35W.

**Output:** 1.5 Amps.

#### Operating Temperature Range:

0°C to +40°C (+32°F to +104°F).

#### Dimensions (charging shoe only) L x W x H:

2.8" x 2.5" x 1.3" (72 x 63 x 33mm).

**Weight:** 2.6oz (75g).

#### Typical Battery Charging Times:

1	96Wh battery:	4hrs
2	96Wh batteries:	8hrs
3	96Wh batteries:	12hrs
4	96W batteries:	16hrs

*Times are for fully-discharged batteries to fully-charged, when powering the charger using the Power Supply Unit. Charge times will be less if batteries are partially discharged. 150Wh batteries will take 50% longer.*



**PAG Ltd.**

565 Kingston Road  
London SW20 8SA

**E** sales@paguk.com

**T** +44 (0)20 8543 3131

**www.paguk.com**

©SEP 2017 PAG Ltd. PAG is the trademark of PAG Ltd.

PAG reserves the right to change the specifications contained herein without notice